

Features

4:3 Display size, Fully IP-65 stainless steel chassis, IP-65 stainless connectors.



Product Specifications

Screen	15" Display	17" Display	19" Display
Resolution	1024x768	1024x768	1024x768
Brightness	300cd/m2	300cd/m2	300cd/m2
Touchscreen	Resistive Touch 4/5 wire		
CPU	Intel J1900 2Ghz Quad Core (Standard)		
RAM	4GB DDR3 (Option 8GB DDR3)		
Storage	M-SATA 32GB (Option 60-500GB Disk)		
I/O Ports	1 x Power Button / 1 x DC IN / 1 x LAN / 2 x USB / 1 x RS232		
Power Input	230VAC Adapter to 12V DC Included with all systems		
Size WxHxD MM	377x288x58 mm	425x361x78 mm	455x367x77 mm
Weight	6.8Kg	8.8Kg	9.7Kg
O/S	Win 10 IoT / Win 10 Pro / Win 7 Emb / Win 7 Pro / Linux		
Operating Temp	0C to +50C		
Humidity (RH)	10% - 90%		
Display Lifetime	Operation Lifetime (LED) Minimum 50.000 Hours Operation life means brightness goes down to 50% to initial brightness. Minimum operation life time is estimated data.		
MTBF	100.000 Hours		
Vibration	1.0G, 5-500Hz Random		
Mounting	VESA 100 / Panel Mount		
Warranty	2 Years		
Approvals	CE / FCC		